

V-R1012-IMD-3GTE specifications

Panel	Number of Panels	2
	Panel Size	10.1" Diagonal
	Resolution	1280 x RGB x 800
	Aspect Ratio	16:10
	Type	LCD Panel
	Brightness	500 cd/m ²
	Contrast	800:1
	Color Gamut	YUV, RGB
	Viewing Angles	150° x 150°
	Backlight type	LED
Features	Compatible Input Formats	SDI / HDSDI Inputs: 525i/59.94,625i/50 720p/23.98,24,25,29.97,30,50,59.94,60 1080p/23.98,23.98sF,24,24sF,25,29.97,30 1035i/59.94,60 1080i/50,59.94,60 3G-SDI Inputs: 3G - Level A and Level B YCbCr, YCbCr+A, RGB, RGB+A 1080p/60,59.94,50 1080p/30,29.97,25,24,23.98,30sF,29.97sF,25sF,24sF,23.98sF 1080i/60,59.94,50
	Loss of Input Curtain	Yes
	Color Temperature	D65, D55 and D93
	Tally	Yes
	Closed Caption	Yes
	Pre-set Gamma points	Yes
	Self-Sensing	Yes
Re-clocked/Re-Shaped	Yes	
Input Connectors	3G-SDI Video Input (Per Screen)	
	1 x BNC Female (75 Ω)	
Output Connectors	3G-SDI Video Output (Active Output, Per Screen)	
	1 x BNC Female (75 Ω)	
Audio Outputs	Embedded Audio SDI	Yes
	Headphones	Yes
	Input Status Display	Yes
Audio OSD	Audio Bars	Yes
	Channels	Yes
Control Inputs	Tally / GPI	Yes
	RS-485/422 w/ Loop-Through	Yes
	Ethernet	No
	Handles/Rack Ears	Yes
Power	Voltage	12 VDC
	Consumption	3.0A @ 12VDC (36 W)
	Power Switch	Yes
	Connector	2-Pin Twist Lock
Compliance	Compliance	CE approved
Environmental	Operating Temperature (C°)	57° F to 104° F (15° C to 40° C)
	Storage Temperature (C°)	14°F to 122°F (-10° C to 50° C)
	Unit dimensions	18.94" W x 6.95" H x 1.74" D
	Weight (Main Body)	6.5 lbs